



(808) 439-6450 office

quotes@solidstatehawaii.com

LUMINAIRE SCHEDULE

| | TYPE | ILLUSTRATION | DESCRIPTION | MANUFACTURER/(OR EQUIVALENT) PART NUMBER | LAMP | WATTS | PRODUCT LINK |
|------------------------|------|--------------|---|--|--------------------------------|-------|------------------------------------|
| TROFFERS AND LAY-INS | A | | 2X4 BACKLIT LED PANEL WITH SELECTABLE LUMENS AND CCT | H.E.WILLIAMS BP-2-4-LS-8-CS-DIM-UNV | 5361 lumens,LED, 80 CRI, 3500K | 48 | BP Spec Sheet |
| | AE | | SIMILAR TO TYPE A WITH 90-MINUTE BATTERY BACK-UP | H.E. WILLIAMS BP-2-4-LS-8-CS-EM/10WKIT CEC-DIM-UNV | 5361 lumens,LED, 80 CRI, 3500K | 48 | BP Spec Sheet |
| | B | | 2X2 BACKLIT LED PANEL | H.E. WILLIAMS BP-2-2-LS-8-CS-DIM-UNV | 4351 lumens,LED, 80 CRI, 3500K | 40 | BP Spec Sheet |
| | BE | | SIMILAR TO TYPE B WITH 90-MINUTE BATTERY BACK-UP | H.E. Williams BP-2-2-LS-8-CS-EM/10WKIT CEC-DIM-UNV | 4351 lumens,LED, 80 CRI, 3500K | 40 | BP Spec Sheet |
| | C | | 2X2 CENTER BASKET TROFFER | H.E. WILLIAMS PT-2-2-L43/840-RA-DIM1-UNV | 4194 lumens,LED,80 CRI, 4000K | 32.2 | PT Spec Sheet |
| | CE | | SIMILAR TO TYPE C WITH 90-MINUTE BATTERY BACK-UP | H.E. WILLIAMS PT-2-2-L43/840-RA-EM/10W-DIM1-UNV | 4194 lumens, LED,80 CRI, 4000K | 32.2 | PT Spec Sheet |
| DOWNLIGHT | D | | 6" DOWNLIGHT WET LOCATION LISTED | H.E. WILLIAMS 6DR-TL-L10-8-27-DIM-UNV-O-M-OF-CS-WET/CC-N-F1 | 982 lumens,LED, 80 CRI, 2700k | 8.7 | 6DR- TL Spec Sheet |
| | DE | | SIMILAR TO TYPE D WITH 90-MINUTE BATTERY BACK-UP | H.E. WILLIAMS 6DR-TL-L10-8-27-EM/7W/IPRTS-DIM-UNV-O-M-OF-CS-WET/CC-N-F1 | 982 lumens, LED, 80 CRI, 2700k | 8.7 | 6DR-TL Spec Sheet |
| WALL/SURFACE MOUNT | F | | 4' LINEAR LED SURFACE MOUNT | H.E. WILLIAMS ASM-4-L25/840-S-A-DIM1-UNV | 2614 lumens,LED,80 CRI, 4000K | 19.5 | ASM Spec Sheet |
| | G | | 4' LINEAR LED WALL/SURFACE MOUNT | H.E. WILLIAMS LLM-4-L6/840-S-RD-DIM1-UNV | 2388 lumens,LED,80 CRI, 4000K | 15.6 | LLM Spec Sheet |
| | GA | | 4' LINEAR LED WALL/SURFACE MOUNT WITH 90 MINUTE BATTERY BACK UP | H.E. WILLIAMS LLM-4-L6/840-S-RD-EM/10WLP-DIM1-UNV | 2388 lumens,LED,80 CRI, 4000K | 15.4 | LLM Spec Sheet |
| STAIRWELL AND CORRIDOR | H | | STAIRWELL FIXTURE | H.E. WILLIAMS SLF-2-L45/840-HIA-OCCWS-FS-505-PP-___ MUST SPECIFY VOLTAGE | 4634 Lumens,LED,80 CRI, 4000K | 34.4 | SLF Specs Sheet |
| | I | | CORRIDOR LIGHTING, DAMP LOCATION | H.E.WILLIAMS 75S-4-L30/840-DIM1-UNV | 2916 lumens,LED,80 CRI, 4000K | 19.7 | 75 Spec Sheet |
| PARKING AND EMERGENCY | J | | AREA LIGHT | H.E.WILLIAMS VA1-L110-7-30-T2-S-BLK-DIM-UNV | 11043 lumens, 70 CRI, 3000K | 110 | VA1 Spec Sheet |
| | X | | EXIT LIGHT CLEAR BACKGROUND, INTERGRAL 90 MINUTE EMERGENCY BATTERY PACK, RECESSED MOUNT, EDGE LIT | H.E. WILLIAMS EXIT/EL/RECESSED-SF-G-CP-AN-EM-D | LED | | EXIT/EL Spec Sheet |

www.solidstatehawaii.com